



MODEL 321NPPM NUCLEAR POWER PLANT TRITIUM IN AIR MONITOR

PURPOSE

The **Model 321NPPM** is a single range tritium in air monitor configured for measuring tritium in the special environmental conditions associated with nuclear plants, especially the CANDU type.

SINGLE MEASUREMENT RANGE

The 321NPPM is a single range instrument capable of measuring up to 4.5 decades

CHOICE OF DUAL 2L OR QUAD 2L ION CHAMBERS

Typical Dual 2L Range:

1 to 19,999 $\mu\text{Ci}/\text{m}^3$ or 0.1 to 1,999.9 MBq/m^3

Typical Quad 2L Range:

0.1 to 1,999.9 $\mu\text{Ci}/\text{m}^3$ or 0.01 to 199.99 MBq/m^3

MAJOR FEATURES OF -NPPM VERSION

- i. Includes automatic recycling dryer to measure tritium oxide specifically, immune to other radioisotopes, including all reactor gases as well as radon
- ii. Gamma compensated chamber design
- iii. Wire-grid ionization chambers are plate-out proof, eliminates tritium contamination and background zero drift
- iv. Completely drift free with automatic electronic zero
- v. Unaffected by variations in temperature or humidity
- vi. Modular design allows you to configure a wide variety of alarms, controls, remote display units, and air sampling units
- vii. Computer compatible outputs to signal operational failure including: loss of sample flow, pump failure, electrical failure (including electronics and the chambers themselves)

EXTREMELY ACCURATE, STABLE, AND SENSITIVE


The 321NPPM has been designed to exhibit sensitivities commensurate with safety requirements for worker exposure in power plants. Accuracy is $\pm 2\%$.

LOW MAINTENANCE

Except for routine attention to the sample line dust filters and preventative maintenance to the sampling pump, the 321NPPM will provide decades of trouble-free service.

OPTIONAL TRITIUM SAMPLING UNIT

Tritium sampling unit allows you to remotely sample up to 24 different locations. Custom configuration available for monitoring multiple locations or rooms.



TRITIUM SPECIFIC MEASUREMENTS
The Model 321NPPM is designed for measuring tritium (HTO) in the presence of other radionuclides. The automatic recycling dryer includes two copper tube columns equipped with heating elements and containing desiccant. When one column is in use, the other is being automatically heated, purged, and cooled to regenerate the desiccant.

Overhoff Technology Corporation

1160 U.S. Highway 50, Milford, Ohio, 45150-9705 USA

Telephone: 513 248 2400 Fax: 513 248 2402

Email: sales@overhoff.com www.overhoff.com



MODEL 321NPPM NUCLEAR POWER PLANT TRITIUM IN AIR MONITOR

TECHNICAL SPECIFICATIONS

MEASUREMENT

	Dual 2L Chambers	Quad 2L Chambers
TYPICAL RANGES	Ci: 1 to 19,999 $\mu\text{Ci}/\text{m}^3$ Bq: 0.1 to 1,999.9 MBq/ m^3	0.1 to 1,999.9 $\mu\text{Ci}/\text{m}^3$ 0.01 to 199.99 MBq/ m^3

ACCURACY $\pm 2\%$ of reading, \pm L.S.D., whichever is greater

DISPLAY 4.5 digital panel meter or LCD color touch-screen

STABILITY AND DRIFT $\pm 1.0 \mu\text{Ci}/\text{m}^3$ long term (thirty days), ambient temperature conditions

RESPONSE RATE
three electronics time constants:
approximately 40 seconds for signals up to about $80 \mu\text{Ci}/\text{m}^3$
approximately 10 seconds for signals from 80 to $10,000 \mu\text{Ci}/\text{m}^3$
approximately 3 seconds for signals above $1.00 \text{mCi}/\text{m}^3$

WARM UP Less than 10 minutes

MEASUREMENT, INTERFACE OUTPUTS
i) 0 - 10 V, linear
ii) Multiple choices of data output: Ethernet, RS-232, USB, 4-20mA

IONIZATION CHAMBER
Choice of dual 2L ionization chambers on one axis, or quad 2L ionization chambers arranged in cruciform pattern for optimal gamma compensation and sensitivity

ALARM SYSTEMS

ALARMS, MALFUNCTION
i) low sample flow
ii) system failure alarm, includes: high and low voltage failure and electrometer failure

LEVEL ALARM includes dual level alarms (alert and high)

ALARM INTERFACE
i) fail safe relay closures
ii) data output (ethernet, RS-232, USB)

SAMPLE FLOW SYSTEM

PUMP diaphragm type 115/230 VAC 50/60 Hz

FLOW RATE 14 LPM maximum @ 0 psia

FLOW METER 0-10 LPM adjustable

DUST FILTER HEPA respirator type

CONNECTION 1/4" stainless steel Swagelok tube fittings

LOW FLOW SENSOR differential pressure switch

ENCLOSURE

SIZE 29.37" [747mm] High x 23.63" [600mm] Wide x 18.62" [473mm] Deep
wall mounted NEMA 12 painted steel enclosure with key lockable door

POWER 115/230 VAC, 50/60 Hz, 50 W max.

WEIGHT 186 lbs [84kg]



MODEL 321NPPM NUCLEAR POWER PLANT TRITIUM IN AIR MONITOR

RECYCLING DRYER UNIT

Desiccant dual copper tube coaxial columns containing desiccant agent. Columns are equipped with Internal heaters for the regeneration of the desiccant

Cycling System motor driven timer to control solenoid valves and the heaters for sequential modes of each column

Column A	Column B
In use	1. heat column
In use	2. purge vapor
In use	3. cool column

The sequence of events takes six hours for completion, whereupon the sequence recommences for the opposite column.

VISUAL INDICATORS

Status Indicator Rotary pointer knob indicates different states of the sample/regenerate process for both desiccant columns


Low Flow Indicator purge pump low flow alarm will indicate when flow falls below 2 LPM

Power 115/230 V, 50/60 Hz, 1500 Watts

Circuit Protection 15 amp circuit breaker/power ON/OFF switch

Physical Size 30" [762mm] W x 46.75" [1187.5mm] H x 13.5" [343mm] Deep wall mounted painted steel enclosure with key lockable door

Weight 245 lbs [111 kg]





MODEL 321NPPM NUCLEAR POWER PLANT TRITIUM IN AIR MONITOR

TRITIUM SAMPLING UNIT (OPTIONAL)

TRITIUM SAMPLING UNIT SYSTEM PERFORMANCE

Pump	115/230 VAC, 50/60 Hz
Flow Rate	89 LPM Maximum at 0 psia
Flow Meter	10-100 LPM
Dust Filter	HEPA respirator type
Pressure	0.1 – 2 atmospheres
Connections	1/4" stainless steel Swagelok fittings
Low Flow Sensor	differential pressure switch
Vacuum Sensor	vacuum switch

CONTROLS

Power Control	ON/OFF toggle switch for power
Pump Control	ON/OFF maintained pushbutton switch for power to pump
Sample Control	MAIN/REMOTE maintained pushbutton switch for control unit selection
Valve Selection	controlled by a rotary switch

VISUAL INDICATORS


Manifold Low Flow	red LED, "on" when purge pump flow fails or falls below 2 LPM.
Connections	1/4" stainless steel Swagelok tube fittings

ENVIRONMENTAL

Temperature	-40° C to +65° C Storage 0° C to +50° C Operating
Humidity	0 – 95 % RH
Air Conditioning	Ventilation or air conditioning is not required.

PHYSICAL

Physical Size	23.62"[600mm]Wide x 25.75" [654mm] High x 15.16" [385mm] Deep NEMA 4
Power	120VAC, 60Hz, 1Ph, 15A
Weight	101 lbs (46 kg)





MODEL 321NPPM NUCLEAR POWER PLANT TRITIUM IN AIR MONITOR

REMOTE DISPLAY UNIT (OPTIONAL)

REMOTE DISPLAY / CONTROL UNIT SYSTEM CONTROLS

- Power Control** ON/OFF toggle switch for power to unit
- Pump Control** ON/OFF maintained pushbutton switch for power to pump
- Sample Control** MAIN/REMOTE maintained pushbutton switch for control unit selection
- Valve Selection** Valve selection controlled by PLC touch screen

VISUAL INDICATORS

- PLC Touch Screen** Displays Tritium Concentration, Alarm Status

- Power** 120VAC, 60Hz, 1Ph, 2A


ENVIRONMENTAL

- Temperature** -40° C to +65° C Storage
0° C to +50° C Operating
- Humidity** 0 – 95 % RH
- Air Conditioning** Ventilation or air conditioning is not required.

PHYSICAL

- Physical Size** 23.62" [600mm] W x 25.75" [654mm] High x 15.16" [385mm] Deep Excluding Hardware
- NEMA Rating** NEMA 4
- Power** 120VAC, 60Hz, 1Ph, 2A
- Weight** 66 lbs (30 kg)

Remote Display Unit for two monitors, other/custom configurations available



Released 10/22/20